

**NAME**

CURLOPT\_STREAM\_DEPENDS – set stream this transfer depends on

**SYNOPSIS**

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_STREAM_DEPENDS, CURL *dephandle);
```

**DESCRIPTION**

Pass a CURL \* pointer in *dephandle* to identify the stream within the same connection that this stream is depending upon. This option clears the exclusive it and is mutually exclusive to the *CURLOPT\_STREAM\_DEPENDS\_E(3)* option.

The spec says "Including a dependency expresses a preference to allocate resources to the identified stream rather than to the dependent stream."

This option can be set during transfer.

*dephandle* must not be the same as *handle*, that will cause this function to return an error. It must be another easy handle, and it also needs to be a handle of a transfer that will be sent over the same HTTP/2 connection for this option to have an actual effect.

**DEFAULT**

NULL

**PROTOCOLS**

HTTP/2

**EXAMPLE**

TODO

**AVAILABILITY**

Added in 7.46.0

**RETURN VALUE**

Returns CURLE\_OK if the option is supported, and CURLE\_UNKNOWN\_OPTION if not.

**SEE ALSO**

**CURLOPT\_STREAM\_WEIGHT(3), CURLOPT\_STREAM\_DEPENDS\_E(3),**